

# Amish Hand-Scraped®

## PRODUCT SPECIFICATION

HomerWood's Amish Hand-Scraped floors offer an exceptionally striking, one-of-a-kind look. A true work of art, each premium plank is uniquely hand-scraped by experienced Amish craftsmen, whose creativity combined with nature assures that no two planks are the same – a highly desirable feature of our hand-scraped floors.



**3/4" Solid\***



**5/8" Engineered\***

### Product Information

Construction	Solid Engineered: 5/8" Sawn Face, Multi-Ply Baltic Birch	
Class of Material	Class C	
Overall Thickness	Solid: Engineered:	3/4" 5/8" with a 4 mm wear layer (nominal)
End/Edge Detail	Prefinished, Four-Sided Micro Bevel Unfinished, Square Edges/Ends	
Lengths	Solid: Engineered:	Long, Random, 1' – 7' Long, Random, 1' – 8'
Finish	UV-Cured Urethane with Aluminum Oxide	
Gloss	Satin (Urethane Only)	
Installation	Solid: Engineered:	Nail Down / On and Above Grade Staple, Glue or Float / On, Above, and Below Grade (Radiant Heat: NWFA Guidelines)
Species	Black Walnut, Hickory, White Oak	
Relative Species Hardness - NWFA Janka Test	1820 – Hickory 1450 – Hard Maple 1360 – White Oak 1010 – Walnut 950 – Cherry	
Use	Residential or Commercial	
Certification	FloorScore®	

### Product Features

Style	Character
Texture	Hand-Scraped
Cut	Plain Sawn
Color Options	Butter Rum, Espresso, Graphite, Natural, Saddle, Turmeric <i>Some color options are only available in one species. Consult product catalog.</i>
Accessory Options	Reducer Strip, Threshold, Stair Nose, Quarter Round, T-Molding

### Packaging

Plank Width		3"	4"	5"	6"	7"	8"
Sq. Ft. per Carton-	Solid: Engineered:	14 ft <sup>2</sup> 20 ft <sup>2</sup>	18.5 ft <sup>2</sup> 26.5 ft <sup>2</sup>	23.5 ft <sup>2</sup> 33 ft <sup>2</sup>	14 ft <sup>2</sup> 20 ft <sup>2</sup>	N/A 23 ft <sup>2</sup>	N/A 26.5 ft <sup>2</sup>
Weight -	Solid: Engineered:	38 – 48 lbs. 48 lbs.	50 – 63 lbs. 64 lbs.	64 – 80 lbs. 80 lbs.	38 – 48 lbs. 48 lbs.	N/A 56 lbs.	N/A 64 lbs.

### Testing

Test	Method	Result
Critical Radiant Flux	ASTM-E-648-17	Class 1
Formaldehyde Emission	ASTM-D-6007	BLQ (Below Limit of Quantitation)
Specific Optical Density of Smoke	ASTM-E-662	Average 438 DM (Non-flaming and Flaming modes)

### Necessary Reading

Warranty - 50-Year Residential 3-Year Commercial Lifetime Structural	<a href="http://www.homerwood.com/about-our-floors/warranty/">http://www.homerwood.com/about-our-floors/warranty/</a>
Installation Instructions	<a href="http://www.homerwood.com/about-our-floors/installation/">http://www.homerwood.com/about-our-floors/installation/</a>
Trim Installation Instructions	<a href="http://www.homerwood.com/about-our-floors/installation/">http://www.homerwood.com/about-our-floors/installation/</a>
Maintenance Information	<a href="http://www.homerwood.com/about-our-floors/maintenance-and-care/">http://www.homerwood.com/about-our-floors/maintenance-and-care/</a>

\*Profile images show the difference between construction types, they are for reference only and will not represent our various surface treatments. Please see our website for visual aids on surface treatment.