

Wire Brushed & Mixed Widths

PRODUCT SPECIFICATION

Distressed wood, and the soft texture of wire brushing, continue to appeal to today's discerning consumers. The varied tones and random patterns capture the essence of vintage reclaimed floors. These visuals create a unique floor that blends wire brushed texture, distinct color liming and mixed widths.



3/4" Solid*



5/8" Engineered*

Product Information

| | | |
|--|--|--|
| Construction | Solid Engineered: 5/8" Sawn Face, Multi-Ply Baltic Birch | |
| Class of Material | Class C | |
| Overall Thickness | Solid: Engineered: | 3/4" 5/8" with a 4 mm wear layer (nominal) |
| End/Edge Detail | Prefinished, Four-Sided Micro Bevel Unfinished, Square Edges/Ends | |
| Lengths | Solid: Engineered: | Long, Random, 1' – 7' Long, Random, 1' – 8' |
| Finish | UV-Cured Urethane with Aluminum Oxide | |
| Gloss | Satin (Urethane Only) | |
| Installation | Solid: Engineered: | Nail Down / On and Above Grade Staple, Glue or Float / On, Above, and Below Grade (Radiant Heat: NWFA Guidelines) |
| Species | Hickory, White Oak | |
| Relative Species Hardness - NWFA Janka Test | 1820 – Hickory 1450 – Hard Maple 1360 – White Oak 1010 – Black Walnut 950 – Cherry | |
| Use | Residential or Commercial | |
| Certification | FloorScore® | |

Product Features

| | |
|-------------------|--|
| Style | Character |
| Texture | Wire Brushed |
| Cut | Plain Sawn |
| Color Options | Amber Cover, Naturally Beautiful, Night's Dream, Tonal Drift <i>Some color options are only available in one species and with specific liming. Consult product catalog.</i> |
| Accessory Options | Reducer Strip, Threshold, Stair Nose, Quarter Round, T-Molding |

Packaging

| | | |
|---------------------|-----------------------|--|
| Plank Width | 2.25"/3"/6" Combo | |
| Sq. Ft. per Carton- | Solid: Engineered: | 19.7 ft ² 19.7 ft ² |
| Weight - | Solid: Engineered: | 64 – 67 lbs. 48 lbs. |

Testing

| Test | Method | Result |
|-----------------------------------|---------------|--|
| Critical Radiant Flux | ASTM-E-648-17 | Class 1 |
| Formaldehyde Emission | ASTM-D-6007 | BLQ (Below Limit of Quantitation) |
| Specific Optical Density of Smoke | ASTM-E-662 | Average 438 DM (Non-flaming and Flaming modes) |

Necessary Reading

| | |
|---|---|
| Warranty - 50-Year Residential 3-Year Commercial Lifetime Structural | http://www.homerwood.com/about-our-floors/warranty/ |
| Installation Instructions | http://www.homerwood.com/about-our-floors/installation/ |
| Trim Installation Instructions | http://www.homerwood.com/about-our-floors/installation/ |
| Maintenance Information | http://www.homerwood.com/about-our-floors/maintenance-and-care/ |

*Profile images show the difference between construction types, they are for reference only and will not represent our various surface treatments. Please see our website for visual aids on surface treatment.