

## PRODUCT SPECIFICATION

HomerWood's SoHo Maple Floors are inspired by NYC's "South of Houston" neighborhood, and pay homage to SoHo's artistic community. The natural variation of Hard Maple's heartwood and sapwood is given an artistic treatment with splashes of lively color selections. This wonderful visual compliments a wide range of décor choices, allowing you to become an artist in your own home.



3/4" Solid\*



5/8" Engineered\*

### Product Information

Construction	Solid Engineered: 5/8" Sawn Face, Multi-Ply Baltic Birch	
Class of Material	Class C	
Overall Thickness	Solid: Engineered:	3/4" 5/8" with a 4 mm wear layer (nominal)
End/Edge Detail	Prefinished, Four-Sided Micro Bevel Unfinished, Square Edges/Ends	
Lengths	Solid: Engineered:	Long, Random, 1' - 7' Long, Random, 1' - 8'
Finish	UV-Cured Urethane with Aluminum Oxide	
Gloss	Satin (Urethane Only)	
Installation	Solid: Engineered:	Nail Down / On and Above Grade Staple, Glue or Float / On, Above, and Below Grade (Radiant Heat: NWFA Guidelines)
Species	Hard Maple	
Relative Species Hardness - NWFA Janka Test	1820 - Hickory 1450 - Hard Maple 1360 - White Oak 1010 - Black Walnut 950 - Cherry	
Use	Residential or Commercial	
Certification	FloorScore®	

### Product Features

Style	Character
Texture	Smooth
Cut	Plain Sawn
Color Options	SoHo Black, SoHo Gray, SoHo Red, SoHo White <i>Some color options are only available in one species. Consult product catalog.</i>
Accessory Options	Reducer Strip, Threshold, Stair Nose, Quarter Round, T-Molding

### Packaging

Plank Width		3"	4"	5"	6"	7"	8"
Sq. Ft. per Carton-	Solid: Engineered:	14 ft <sup>2</sup> 20 ft <sup>2</sup>	18.5 ft <sup>2</sup> 26.5 ft <sup>2</sup>	23.5 ft <sup>2</sup> 33 ft <sup>2</sup>	14 ft <sup>2</sup> 20 ft <sup>2</sup>	N/A 23 ft <sup>2</sup>	N/A 26.5 ft <sup>2</sup>
Weight -	Solid: Engineered:	44 lbs. 48 lbs.	58 lbs. 64 lbs.	73 lbs. 80 lbs.	44 lbs. 48 lbs.	N/A 56 lbs.	N/A 64 lbs.

### Testing

Test	Method	Result
Critical Radiant Flux	ASTM-E-648-17	Class 1
Formaldehyde Emission	ASTM-D-6007	BLQ (Below Limit of Quantitation)
Specific Optical Density of Smoke	ASTM-E-662	Average 438 DM (Non-flaming and Flaming modes)

### Necessary Reading

Warranty - 50-Year Residential 3-Year Commercial Lifetime Structural	<a href="http://www.homerwood.com/about-our-floors/warranty/">http://www.homerwood.com/about-our-floors/warranty/</a>
Installation Instructions	<a href="http://www.homerwood.com/about-our-floors/installation/">http://www.homerwood.com/about-our-floors/installation/</a>
Trim Installation Instructions	<a href="http://www.homerwood.com/about-our-floors/installation/">http://www.homerwood.com/about-our-floors/installation/</a>
Maintenance Information	<a href="http://www.homerwood.com/about-our-floors/maintenance-and-care/">http://www.homerwood.com/about-our-floors/maintenance-and-care/</a>

\*Profile images show the difference between construction types, they are for reference only and will not represent our various surface treatments. Please see our website for visual aids on surface treatment.