

PRODUCT SPECIFICATION



1/2" Engineered*

Product Information

Construction	Engineered: 1/2" Sawn Face, Multi-Ply Baltic Birch	
Class of Material	Class C	
Overall Thickness	Engineered:	1/2" with a 3 mm wear layer (nominal)
End/Edge Detail	Prefinished, Four-Sided Micro Bevel * Unfinished, Four-Sided Micro Bevel *	
Lengths	Engineered:	Long, Random, 1' – 8'
Finish	UV-Cured Urethane with Aluminum Oxide	
Gloss	Matte (Urethane Only)	
Installation	Engineered:	Staple, Glue or Float / On, Above, and Below Grade (Radiant Heat: NWFA Guidelines)
Species	Hickory, White Oak	
Relative Species Hardness - NWFA Janka Test	1820 – Hickory 1360 – White Oak	
Use	Residential or Commercial	
Certification	FloorScore®	

Product Features

Style	Character Hickory Prime White Oak
Texture	Smooth
Cut	Plain Sawn
Color Options	Hickory: Natural, Umber, Sand, Mink White Oak: Natural, Frost, Taupe, Shale, Dove, Shade
Accessory Options	Reducer Strip, Threshold, Stair Nose, Quarter Round, T-Molding

Packaging

Plank Width		6"
Sq. Ft. per Carton-	Engineered:	23
Weight -	Engineered:	46 lbs.

Testing

Test	Method	Result
Critical Radiant Flux	ASTM-E-648-17	Class 1
Formaldehyde Emission	ASTM-D-6007	BLQ (Below Limit of Quantitation)
Specific Optical Density of Smoke	ASTM-E-662	Average 438 DM (Non-flaming and Flaming modes)

Necessary Reading

Warranty - 50-Year Residential 3-Year Commercial Lifetime Structural	http://www.homerwood.com/about-our-floors/warranty/
Trim Installation Instructions	http://www.homerwood.com/about-our-floors/installation/
Maintenance Information	http://www.homerwood.com/about-our-floors/maintenance-and-care/

*Profile image is for reference only and will not represent width or surface.