

PRODUCT SPECIFICATION

Our Smoked Specialties floors offer dramatic, rich and alluring visual elements that add design and depth to a room. The natural figuring of the grain is accented by gently flaming the wood, board by board. The heat from the open flame caramelizes the sugars in the sapwood, creating a shadowed look that can't be imitated.



3/4" Solid*



5/8" Engineered*

Product Information

Construction	Solid Engineered: 5/8" Sawn Face, Multi-Ply Baltic Birch	
Class of Material	Class C	
Overall Thickness	Solid: Engineered:	3/4" 5/8" with a 4 mm wear layer (nominal)
End/Edge Detail	Prefinished, Four-Sided Micro Bevel Unfinished, Square Edges/Ends	
Lengths	Solid: Engineered:	Long, Random, 1' – 7' Long, Random, 1' – 8'
Finish	UV-Cured Urethane with Aluminum Oxide	
Gloss	Satin (Urethane Only)	
Installation	Solid: Engineered:	Nail Down / On and Above Grade Staple, Glue or Float / On, Above, and Below Grade (Radiant Heat: NWFA Guidelines)
Species	Hickory, White Oak	
Relative Species Hardness - NWFA Janka Test	1820 – Hickory 1450 – Hard Maple 1360 – White Oak 1010 – Walnut 950 – Cherry	
Use	Residential or Commercial	
Certification	FloorScore®	

Product Features

Style	Character
Texture	Smooth, Hand-Scraped, Wire Brushed, Smoked
Cut	Plain Sawn
Color Options	Carbonera, Cinnamon, Graphite, Natural, Red Saddle, Sandstone, Sandgate, Schenna, Turmeric <i>Some color options are only available in one species, or with multiple surface treatments. Consult product catalog.</i>
Accessory Options	Reducer Strip, Threshold, Stair Nose, Quarter Round, T-Molding

Packaging

Plank Width		3"	4"	5"	6"	7"	8"
Sq. Ft. per Carton-	Solid: Engineered:	14 ft ² 20 ft ²	18.5 ft ² 26.5 ft ²	23.5 ft ² 33 ft ²	N/A 20 ft ²	N/A 23 ft ²	N/A 26.5 ft ²
Weight -	Solid: Engineered:	45 – 48 lbs. 48 lbs.	60 – 63 lbs. 64 lbs.	76 – 80 lbs. 80 lbs.	N/A 48 lbs.	N/A 56 lbs.	N/A 64 lbs.

Testing

Test	Method	Result
Critical Radiant Flux	ASTM-E-648-17	Class 1
Formaldehyde Emission	ASTM-D-6007	BLQ (Below Limit of Quantitation)
Specific Optical Density of Smoke	ASTM-E-662	Average 438 DM (Non-flaming and Flaming modes)

Necessary Reading

Warranty - 50-Year Residential 3-Year Commercial Lifetime Structural	http://www.homerwood.com/about-our-floors/warranty/
Installation Instructions	http://www.homerwood.com/about-our-floors/installation/
Trim Installation Instructions	http://www.homerwood.com/about-our-floors/installation/
Maintenance Information	http://www.homerwood.com/about-our-floors/maintenance-and-care/

*Profile images show the difference between construction types, they are for reference only and will not represent our various surface treatments. Please see our website for visual aids on surface treatment.